

12 Series Shocks

Shock Facts:

6" Body dia: ... 1.820

7" Body dia: 1.820

Thread pitch: 8 per inch

Bore dia front: 38mm 1.500

Bore dia rear: 38mm 1.500

Front Stroke: 6 and 7 inches

Shaft size: .471 dia.

Mounting: .500 shock eye both ends

Base Valve Option: No

SRT Piston Option: Yes

6 inch Open/Closed: 18.00 open
11.00 closed

7inch Open/Closed: 20.0 open
13.0 closed

Shock Valving

Standard Valving

Standard:

1030 100 psi

3010 100 psi

2020 100 psi

2040 100 psi

3030 100 psi

3010 100 psi

4020 100 psi

3060 150 psi

Standard valve shocks use a standard 4 bleed shim and have no low speed nose built on the shock curve.

Custom valved shock are modified to perform or make the car do something different. Custom valved shocks usually have more low speed control.

Custom Valving

Custom:

RF:

RF1-40/130 100 psi (6-1.5)

RF1-50/130 100 psi (7-1.5)

RF1-60/130 @ 100 psi

RF1-75/130 @ 100 psi

LF:

LF 140-160 100 psi (3-3)

LF1-30/160 @ 100 psi

LF1-40/160 @ 100 psi

RR:

RR 150/160 100 psi (3-3)

RR1-40 @ 100 psi (6-2)

LR:

LR 125-225 125 psi

LR 100-300 150 psi

LR1-40-300 @ 150 psi

Shocks are Rebound / Compression on valving